- 7.5 Storing channelizing devices along any roadway is prohibited without approval of the Engineer.
- 7.6 Type 3 object markers (VP-1) are required for barrier flare\tangent points.
- 7.7 The appropriate channelizing devices (inculding approved barrier) to separate opposing traffic shall be as shown on the plans or as directed by the Engineer.

8.0 PAVEMENT MARKINGS

- 8.1 Pavement markings no longer applicable shall be completely removed or obliterated. Temporary markings shall be used as necessary. Operations less than 12 hours or undertaken during the daytime may require that the permanent markings be temporarily covered with black tape as specified below.
- 8.2 Pavement marking lines adjacent to any lane transition or lane closure taper shall be removed (or covered with SHA approved black pavement marking tape) as depicted on TTCTA for over 12 hours or nighttime use, unless otherwise directed by the Engineer. Pavement marking lines shall be re—installed (or uncovered) prior to re—opening the closed lane(s).
- 8.3 Temporary markings on intermediate pavement surfaces shall be paint placed to full dimensions per the Contract Documents, (i.e. continuous double yellow center lines; single dashed yellow center line 10' segments, 30' gaps to denote passing when allowed; lane lines 10' segments, 30' gaps).
- 8.4 On straight sections of roadway with full dimension center and*or lane lines, but without edge lines, channelizing drums may be used to delineate the edge of the roadway and may be spaced up to 500' apart where no undue hazards exist and when directed by the Engineer. On curve sections, this spacing shall be reduced to a value equal to the posted speed limit, unless otherwise directed by the Engineer.

SPECIFICATION 104	CATEGORY CODE ITEMS		Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES			
APPROVED	APPROVED DIRECTOR - OFFICE OF TRAFFIC AND SAFETY					
	APPROVAL • SHA REVISIONS APPROVAL 9-10-96	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION APPROVAL 9-27-96	GENER	GENERA	AL NOTES	
	REVISED 10-1-01	REVISED				
DIGITALISMAN	REVISED REVISED	REVISED REVISED	STANDARD	NO.	MD	104.00–10